85503

SECURE VIEW™ DC BATTERY BACKUP BELT DRIVE WI-FI® GARAGE DOOR OPENER

Integrated HD camera lets you see who's coming and going in your garage.

Smartphone not included

myQ key **ENABLES FREE IN-GARAGE DELIVERY FOR AMAZON PRIME MEMBERS**
Key by Amazon available in select markets.
See myQ.com/key-by-Amazon for details.

KEY FEATURES

BUILT-IN CAMERA begins recording 1080p HD video when motion is detected-even at night-and allows for 2-way audio.

VIDEO STORAGE The myQ® App will send motion alerts and view live stream of your garage for free. 7-Day and 30-Day video storage options are available via a monthly or yearly subscription.

BUILT-IN WI-FI for the easiest way to connect to the garage.

myQ MOBILE APP lets users close from anywhere. Open for anyone. Get alerts.

INTEGRATED BATTERY BACKUP ensures garage access even when the power's out.

BELT DRIVE SYSTEM AND QUIET DC MOTOR provide smooth operation and long-lasting service.

SOFT START/STOP for smooth operation.

SECURITY+ 2.0® Safeguards garage access by sending a new code with every click.

POSILOCK® electronically protects against forced openings.

TIMER-TO-CLOSE can be programmed to close the door after a set amount of time.

ALERT-2-CLOSE signals when a door is being closed by myQ®.

MOTION DETECTOR lights the way automatically.

THE PROTECTOR SYSTEM® Invisible light beam auto-reverses the door if there is an obstruction.

WARRANTY lifetime motor and belt, 5-year parts, 1-year battery, camera, and accessories.

INCLUDED ACCESSORIES:

SMART CONTROL PANEL® 880LMW
LCD Display enables simple programming and adjustment of settings.

3-BUTTON REMOTE CONTROL 893MAX
Operates up to 3 openers or myQ Light Accessories.

INTEGRATED BATTERY BACKUP 485LM
Powers up the opener when the power's out.

POWERFUL ADD-ONS:

REMOTE LIGHT CONTROL 825LM
Plug in any lamp to this device to control it with a smartphone or garage remote.

MINI UNIVERSAL REMOTE CONTROL 374UT
Compact and portable to provide quick, easy garage access.

WIRELESS KEYLESS ENTRY 877MAX
Provides convenient, secure access from outside the garage with a 4-digit PIN.

LiftMaster®

MASTERFUL ENGINEERING.

85503

SECURE VIEW™ DC BATTERY BACKUP BELT DRIVE WI-FI® GARAGE DOOR OPENER

MOTOR
- 12V DC
- 53 RPM
- Automatic Thermal Protection
- Permanent Lubrication

POWER
- 120V AC
- 60 Hz Voltage
- 2.7A Current Rating
- UL® Listed
- 6' Power Cord (3-Prong)

CAMERA
- 120V AC
- 60Hz Voltage
- Operating Temp: -13°F to 131°F
- Resolution: 1080P

MECHANICS
- **Steel Chassis, T-Rail and Trolley**
- **Full Reinforced Belt Drive Mechanism** (63:1 Gear Reduction and Adjustable Door Arm)
- **Auto-Force** Adjustment for Changing Weather and Environmental Conditions
- **Electronic Limits** for Easy Setup
- **DC Wi-Fi Logic Board** with Built-In Surge Suppressor (for Replacement Logic Boards, Order Part 050DCTWF)

DIMENSIONS

Rail Options	7'	8'	10'
Installed Length	125"	140"	164"
Max. Opening	7'6"	8'6"	10'6"

Headroom Clearance Required: 2"

SPEED
9" Per second for door to move upward

6.5" Per second for door to move downward

STANDARD SPECS.

SECURITY

SECURITY+ 2.0®
RADIO CONTROLS

Operating Range: ~200'

Operating Temperature: -40°F to 150°F

3-Button Remote Control (893MAX)
- Remote Control: 310, 315 and 390 MHz Tri-Band**
- Garage Door Opener: Frequency Agile on 310, 315 and 390 MHz
- Anti-Burglary Coding

**Tri-band on Security+ 2.0 coding only. Premium remote control is backwards compatible to all LiftMaster® openers manufactured since January 1993.

ENCRYPTED CONTROLS

Smart Control Panel® (880LMW)
- Timer-to-Close
- Program Remote Controls, Keypads and myQ Accessories
- Maintenance Alert System
- Easy Wi-Fi Setup

SMART

myQ® RADIO
902–928 MHz
50-Channel FHSS
(Frequency Hopping Spread Spectrum)

- Provides 2-way communication from garage door opener and myQ Accessories.
- Enables monitoring and control of garage door openers and lighting controls via smart device.

HOMELINK® COMPATIBLE (VERSION 4.0 OR HIGHER***)
***May require an external adapter depending on the model and year of your vehicle. Visit HomeLink.com for additional information.

ELECTRICAL

LIGHTING
100W 100W

- Max. 2 100-Watt Lightbulbs
- Adjustable Time
- Enhanced CFL (Compact Fluorescent) Compatible, Max. 26 Watts
- Disabled in Battery Backup Mode

SHIPPING.

SHIPPING WEIGHT
(in lbs.)

22 HEAD

17 RAIL

CARTONS (2)
CARTON 1: 19.81" x 11.94" x 11.19"
- Garage Door Opener Head (85503)
- Battery (485LM)
- Smart Control Panel (880LMW)
- 3-Button Remote Control (893MAX)
- The Protector System® Safety Reversing Sensors

CARTON 2: 10'4" x 5" x 5" (for 7' Rail)
- Assembled Solid-Steel Belt T-Rail

SAFETY FEATURES.

- Integrated HD Camera streams 1080P video straight to your smartphone
- Night-vision and a glare-resistant lens automatically adjusts to the light when your garage is opened
- Alert-2-Close/Unattended Close Operation
- Motion Detection Feature on Control Panel
- Ventilation/Pet Opening
- Down Safety Reverse
- Integrated Battery
- Safety Beam Obstruction Turns Lights On
- Maintenance Alert System
- Garage Door Opener Capacity of up to 40 Remote Controls, 4 Wireless Keyless Entry Systems and 16 MyQ Devices

WARNING: to reduce the risk of injury to persons—ONLY enable Timer-to-Close and myQ remote operation features when opener is installed on a sectional door.

© 2020 The Chamberlain Group, Inc. All Rights Reserved. LiftMaster, the LiftMaster logo, myQ and the myQ logo are registered trademarks of The Chamberlain Group, Inc. 300 Windsor Drive, Oak Brook, IL 60523 LiftMaster.com

LMGDENPG85503 08/20

UL® and the UL logo are trademarks of UL LLC © 2020 All Rights Reserved. Wi-Fi® is a registered trademark of Wi-Fi Alliance. HomeLink® and the HomeLink House® logo are registered trademarks of Gentex Corporation. Secure View is a registered trademarks of The Chamberlain Group, Inc. The State of California has not endorsed these or any other garage door openers.

LiftMaster®